



7k, 9k, 12k, 16k, 18k



YR-E17 de serie

YR-E16A opcional

YR-H71 opcional

RE-02 opcional



Modelo / Unidad interior			AB072MBERA	AB092MBERA	AB122MBERA	AB162MBERA	AB182MBERA
Capacidad nominal	Refrigeración	kW	2.2	2.8	3.6	4.5	5.6
	Calefacción	kW	2.5	3.2	4	5	6.3
Alimentación	Tensión eléctrica	Fase/V/Hz	1/220-230/50-60	1/220-230/50-60	1/220-230/50-60	1/220-230/50-60	1/220-230/50-60
Rendimiento	Caudal de aire	m ³ /h	840	840	840	840	840
	Presión sonora (Alta/Media/Baja)	dB (A)	42/37/33	42/37/33	42/37/33	44/39/34	44/39/34
Dimensiones y peso	Netas (An/Pr/Al)	mm	817/620/260	817/620/260	817/620/260	817/620/260	817/620/260
	Embalaje (An/Pr/Al)	mm	1015/695/278	1015/695/278	1015/695/278	1015/695/278	1015/695/278
	Neto/bruto	kg	21/23	21/23	21/23	21/23	21/23
	Modelo panel		P2B-1055IB	P2B-1055IB	P2B-1055IB	P2B-1055IB	P2B-1055IB
	Panel netas (An/Pr/Al)	mm	1055/680/8	1055/680/8	1055/680/8	1055/680/8	1055/680/8
Datos de instalación	Línea de líquido	Pulgadas / mm	1/4" / 6.35	1/4" / 6.35	1/4" / 6.35	1/4" / 6.35	1/4" / 6.35
	Línea de gas	Pulgadas / mm	3/8" / 9.52	3/8" / 9.52	1/2" / 12.7	1/2" / 12.7	1/2" / 12.7
Mando	Con cable (O-opcional, S-serie)		YR-E17 (S)	YR-E17 (S)	YR-E17 (S)	YR-E17 (S)	YR-E17 (S)
			YR-E16A (O)	YR-E16A (O)	YR-E16A (O)	YR-E16A (O)	YR-E16A (O)
	Infrarrojo (O-opcional, S-serie)		YR-H71 (O)	YR-H71 (O)	YR-H71 (O)	YR-H71 (O)	YR-H71 (O)